



## Experience LifeSize Presence.

Telepresence is the experience of being present – an immersive video communications experience that allows you to meet with remote participants as if you’re sitting in the same room. LifeSize images in high definition, natural eye contact with superior camera technology and placement, along with crystal clear audio enable a rich communications experience.

### LifeSize® Conference™ is telepresence done right.

Telepresence is no longer limited to the executive board room. LifeSize Conference is the first telepresence suite that can be tailored to your environment – providing just what you need, where you need it. LifeSize Conference offers telepresence quality, unique flexibility and unmatched price performance.

### Immersive telepresence quality

LifeSize Conference delivers stunning high definition video – 30 frames per second and 1280x720 screen resolution. Wide band, natural audio and built-in data sharing enrich your communications experience.

### Unique flexibility

LifeSize Conference includes three HD codecs, multiple HD cameras and the LifeSize Phone. LifeSize Conference accommodates three HD monitors, one data monitor, and a touch screen control panel. Like all LifeSize systems, LifeSize Conference is standards based and fully interoperable to easily fit into your existing environment. Users can choose between LifeSize Conference telepresence mode or LifeSize® Room™ mode - giving you the flexibility to create a telepresence experience or to use the full functionality of a LifeSize Room system for both point-to-point and multipoint calls. LifeSize Conference scales to meet your specific needs.

### Unmatched price performance


LifeSize Conference brings telepresence within reach. LifeSize delivers price performance that enables telepresence to be deployed beyond the boardroom.

## LifeSize Conference Key Features

**Video Quality** High Definition Telepresence Quality  
1280x720 - 30 fps  
16x9 format

**HD Monitors**   
3 Video, 1 Data

**HD Cameras**   
Multiple

**High Definition Audio** 

**External Audio, Video & Data Input/Output** Audio: 4 in, 3 out  
Video: 9 in, 6 out  
Data: 2 in, 2 out

**Point-to-Point HD Telepresence** 

**Conference Room Telepresence Configuration** 

**( LifeSize. Be present. )**

# Product Specifications - LifeSize® Conference™

## System Components

3 x LifeSize Room Codecs  
4 x LifeSize Cameras\*  
1 x LifeSize Phone  
1 x LifeSize Conference software\*\*  
Power supplies  
Cables  
\* 4th LifeSize Camera used as full PTZ camera for LifeSize Room mode  
\*\* Software applicable to AMX control panel

## System Modes

LifeSize Conference  
- Multi-codec HD telepresence solution  
LifeSize Room  
- Dual monitor HD videoconferencing solution  
(See LifeSize Room product data sheet)

## Communications

3.0 Mbps – 18 Mbps  
(1.0Mbps – 6.0Mbps per codec)

## Multiple Displays

Support for three high definition video monitor displays  
Support for one high definition data monitor display  
Any high definition 720p component VGA monitor (1280x720) is supported  
LifeSize recommends all three video monitors be identical in manufacturer and size to guarantee quality of the video display  
LifeSize recommends the following size for all monitors:  
All three video monitors should be between 58" and 65"  
The data monitor should be between 42" and 50"

## High Definition Camera

Support for three cameras attached to three codecs (primary input)  
Resolution: 1280x720, 30fps  
Camera supports locked position and focus  
3 x 7.5M/25 ft. cable

## Video Specifications / Video Resolution

1 Mbps or higher (1280x720 pixels) per codec

## Video Standards

H.261, H.263, H.263+, H.264 and H.239

## Video Formats

High Definition, 16x9 aspect ratio

## Video Inputs (9 Inputs)

4 x High Definition Cameras  
- One per codec in primary camera inputs  
- One for center codec for LifeSize Room mode (future)  
2 x Composite/VGA  
- Center codec only  
2 x S-Video  
- Center codec only  
1 x VGA in  
- Center codec only  
- Supports up to 1280x1024

## Video Outputs (6 Outputs)

4 x Component/VGA  
- One per codec to primary video monitors  
- One from center codec to secondary data monitor  
1 x S-Video  
- Center codec only  
1 x Composite/RCA  
- Center codec only

## Fully Integrated, High Definition Audio Conference Phone

16 omni-directional microphones in Circular Array with beam forming technology for high quality performance  
100Hz up to 16kHz for wideband support  
Powered directly by center codec through cable

## Audio Standards

G.711, G.722, G.722.1C  
(Polycom® Siren14™).  
G.728, G.729, MPEG-4 AAC-LC

## Audio Inputs (4 Inputs)

1 x RJ-45 for LifeSize Phone  
1 x RCA line level in  
1 x RCA line level input (L+R)  
1 x 3.5mm Mic In  
- All inputs above are attached to center codec only

## Audio Outputs (3 Outputs)

1 x RJ-45 for LifeSize Phone  
1 x Main audio output (L+C+R)  
1 x RCA line level output  
- All outputs above for center codec only

## User Interface

Provided through third party control panel with uniquely designed LifeSize Conference software  
Directory/Address book  
Hierarchical address support  
Password protection  
Supported AMX Solution Controller  
- NXT-CV7 7" Modero Widescreen Viewpoint Touch Panel  
- NI-3100 NetLinx Integrated Controller  
- Associated power supply and mounting brackets

## Security

Flash-based web management tool  
Admin and User level passwords  
SNMP security alerts  
Ability to disable HTTP, SSH and TelNet services

## Power

AC Voltage per LifeSize codec  
100-240V, 50-60 Hz, 2.5A

## Environmental Data

Per LifeSize codec:  
Operating Temperature: 0°C (32°F) to 35°C (95°F)  
Operating Humidity: 15% to 85%, non-condensing  
Storage temperature: -20°C (-4°F) to 60°C (140°F)  
Storage humidity: 10% to 90%, non-condensing

Regulatory Model Number  
LFZ-001

For additional information: [www.lifesize.com/support](http://www.lifesize.com/support)

Information contained in this document is preliminary and subject to change without notice. LifeSize is a registered trademark or trademark of LifeSize Communications in the U.S. and other countries. Copyright 2009. All rights reserved. April 2009.



Corporate Headquarters: 901 S. Mopac Expressway Building 3, Suite 300 Austin, Texas 78746 USA  
Phone: +1 512 347 9300  
Fax: +1 512 347 9301  
Email: [info@lifesize.com](mailto:info@lifesize.com)  
[www.lifesize.com](http://www.lifesize.com)

EMEA: LifeSize Communications  
Toll-Free Europe  
008000 999 09 799

APAC: LifeSize Communications  
Hong Kong  
Phone: +852 8239 3695